

QI ECO R76 WH 430TED 8530 IP44 36°

| Light technic | |
|---|----------------------------|
| Product ID | 3234453 |
| Beam angle | 38 °, Medium beam 21-40° ° |
| Efficacy | 70 lm/W |
| Luminous flux (lm) | 420 |
| Reflector | High-gloss |
| Colour rendering index CRI | 80-89 |
| Lamp type | LED not exchangeable |
| Light outlet | Direct |
| Light sharing | Symmetric |
| With light source | Yes |
| Colour temperature | 3000.0 - 3000.0 K |
| Rated luminous flux according to IEC 62722-2-1 | 430 lm |
| Colour of light | White |
| Luminous flux | 430.0 - 430.0 lm |
| Rated life time L70/B50 at 25 °C | 50000 Hours |
| Colour consistency (McAdam ellipse) | SDCM3 |
| Light distributor | Refractor lens |
| Technical data | |
| Protection class | II |
| Colour housing | White |
| Surface protection | Powder coating |
| Suitable for lamp power | 6.0 - 6.0 |
| Type of control gear | Electronic transformer |
| Material housing | Aluminium |
| Material cover | Plastic, transparent |
| Degree of protection (IP) | IP44 |
| Control gear included | Yes |
| Max. system power | 8 W |
| Adjustability | Swivelling |
| Rated ambient temperature according to IEC62722-2-1 | -20.0 - 40.0 °C |
| Dimming phase cut-off | Yes |
| Input | |
| Voltage type | AC |



19.04.2024

Subject to changes and printing errors

| | |
|---|-----------------------------|
| Nominal voltage | 220.0 - 240.0 V |
| Installation | |
| Height/depth | 40.5 mm |
| Built-in width | 70 mm |
| Built-in height/depth | 32 mm |
| Length | 88 mm |
| Built-in length | 70 mm |
| Width | 88 mm |
| Can be installed directly into the insulation | Yes |
| Outer diameter | 88 mm |
| Conductor cross section | 0.35 mm ² |
| Connection type | Push-in clamp |
| Suitable for suspended mounting | No |
| Number of poles | 2 |
| Suitable for built-in mounting | Yes |
| Connectable conductor cross section | 0.35 - 1.5 mm ² |
| Type of wiring | Suitable for through wiring |
| Suitable for ceiling mounting | Yes |
| logistics data | |
| Imported by | The Light Group |
| Brand | Quick Install |