

QI ECO R76A LU 430TED 8530 IP44

36°



Light technic	
Product ID	3234454
Beam angle	38 °, Medium beam 21-40° °
Colour temperature	3000 K, 3000 - 3000 K
Colour rendering index (CRI/Ra)	85
Efficacy	70 lm/W
Luminous flux (lm)	420
Lamp efficacy	70 lm/W
Tilt-able	15 °
Reflector	High-gloss
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Rated luminous flux according to IEC 62722-2-1	430 lm
Colour of light	White
Luminous flux	430 - 430 lm
Rated life time L70/B50 at 25 °C	50000 Hours
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Refractor lens
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Protection class	II
Colour housing	Aluminium
Surface protection	Powder coating
Suitable for lamp power	6 - 6
Type of control gear	Electronic transformer
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP44
Control gear included	Yes
Max. system power	8 W
Adjustability	Swivelling



28.07.2021

Subject to changes and printing errors

Rated ambient temperature according to IEC62722-2-1	-20 - 40 °C
Dimming phase cut-off	Yes
Dimming method	Trailing edge
Input	
Voltage type	AC/DC
Strain relief	Yes
Nominal voltage	220 - 240 V
Output	
LED nominal current at constant current	110 - 110 mA
Installation	
Cut-out hole (Ø)	76 mm
Height/depth	40.5 mm
Built-in width	70 mm
Built-in height/depth	32 mm
Length	88 mm
Built-in length	70 mm
Width	88 mm
Can be installed directly into the insulation	Yes
Outer diameter	88 mm
Conductor cross section	0.35 mm ²
Connection type	Plug clamp
Built-in diameter	76 mm
Suitable for suspended mounting	No
Number of poles	2
Suitable for wall mounting	No
Suitable for built-in mounting	Yes
Connectable conductor cross section	0.35 - 1.5 mm ²
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	Quick Install
General data	
GTIN	7070938054584