

SLC BLOCKY R62 WH TED 2700K

CRI90 IP54 24°



SLC Design Blocky is a square recessed ceiling luminaire in contemporary Scandinavian design. Blocky has a distinctively clean look. Placed singly, it is suitable for highlighting a specific area and casts a square beam of light that looks good on a mat surface. Blocky will provide adequate yet energy-efficient illumination of private and commercial spaces when arranged in a row.



Light technic	
Product ID	3234518
Beam angle	24 °, Medium beam 21-40° °
Efficacy	56 lm/W
Luminous flux (lm)	553
MacAdam (SDCM)	3
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	2700.0 - 2700.0 K
Rated luminous flux according to IEC 62722-2-1	560 lm
Colour of light	White
Luminous flux	553.0 - 553.0 lm
Rated life time L70/B50 at 25 °C	50000 Hours
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Luminaire efficacy	56 lm/W
Technical data	
CE	Yes
IP class	IP54
Protection class	II
Colour housing	White
Surface protection	Powder coating
Suitable for lamp power	9.0 - 9.0
Type of control gear	LED operating device current-controlled
Material housing	Aluminium

26.04.2024
Subject to changes and printing errors

Material cover	Plastic, transparent
Degree of protection (IP)	IP54
Covering of the luminaire with thermally insulating material possible	No
Control gear included	Yes
Fit for workplace according to EN 12464-1	No
Max. system power	10 W
Adjustability	Not adjustable
Rated ambient temperature according to IEC62722-2-1	-10.0 - 45.0 °C
Dimming phase cut-off	Yes
Power factor	0.95
Dimming interface	Trailing edge
Input	
Electrical connection (Input)	L`L`N`N quick connection
Voltage type	AC
Nominal voltage	220.0 - 240.0 V
Power factor	0.95
Installation	
Height/depth	103 mm
Built-in width	62 mm
Height	103 mm
Built-in height/depth	43 mm
Length	70 mm, 70 mm
Built-in length	62 mm
Width	70 mm, 70 mm
Outer diameter	70 mm
Conductor cross section	0.35 mm ²
Connection type	Push-in clamp
Suitable for suspended mounting	No
Number of poles	3
Suitable for built-in mounting	Yes
Connectable conductor cross section	0.75 - 2.5 mm ²
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC
F-Pak	
F-pack width	70 mm

26.04.2024
Subject to changes and printing errors

F-pack height	95 mm
F-pack weight	350 g
F-pack length	70 mm
EPREL Data	
EPREL Energy Class	G
D-Pak	
D-pack quantity	30 pcs
D-pack width	475 mm
D-pack length	395 mm
D-pack weight	15200 g
D-pack height/diameter	290 mm
General data	
Pallet length	1200 mm
Rated power	9 W
M-Pak	
M-pack length	135 mm
Number	1
M-pack weight	400 g
M-pack height	90 mm
M-pack width	125 mm