

QI BRIGHT S240 LED 960HF 830 OP



Qi Bright LED ceiling lamp with bracket for fast and easy Installation.
Fasten the bracket to the ceiling, twist the lamp in place.

Light technic	
Product ID	3300006
Beam angle	Extreme wide beam >80° °
Efficacy	80 lm/W
Luminous flux (lm)	960
MacAdam (SDCM)	3
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Light sharing	Symmetric
With light source	Yes
Colour temperature	3000.0 - 3000.0 K
Rated luminous flux according to IEC 62722-2-1	960 lm
Colour of light	White
Light distributor	Diffuser lens/optic/panel
Luminaire efficacy	90 lm/W
Technical data	
CE	Yes
IP class	IP20
Protection class	II
Colour housing	White
Type of control gear	LED operating device current-controlled
Material housing	Plastic
Material cover	Plastic, opal
Degree of protection (IP)	IP20
Control gear included	Yes
Max. system power	12 W
Rated ambient temperature according to IEC62722-2-1	-10.0 - 45.0 °C
Filament test according to IEC 60695-2-11	650 °C - 30 s
Dimming phase cut-off	Yes
No dim function	Yes
Power factor	0.9
Input	



Voltage type	AC
Nominal voltage	200.0 - 240.0 V
Installation	
Height/depth	65 mm
Width	240 mm
Outer diameter	240 mm
Conductor cross section	2.5 mm ²
Connection type	Push-in clamp
Suitable for suspended mounting	No
Number of poles	4
Suitable for built-in mounting	No
Suitable for surface mounting	Yes
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	Quick Install
General data	
Type of grid	Matt