



BRIGHT S240 LED 960HF 830 OP

Qi Bright LED ceiling lamp with bracket for fast and easy Installation.
Fasten the bracket to the ceiling, twist the lamp in place.

Light technic	
Product ID	3300006
Beam angle	Extreme wide beam >80°
Colour temperature	3000 K, 3000 - 3000 K
Colour rendering index (CRI/Ra)	80
Efficacy	80 lm/W
Luminous flux (lm)	960
MacAdam (SDCM)	3
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Rated luminous flux according to IEC 62722-2-1	960 lm
Colour of light	White
Rated life time L80/B10 at 25 °C	50000 Hours
Light distributor	Other
Luminaire efficacy	90 lm/W
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
CE	Yes
Dimmable	No
IP class	IP20
RoHs	Yes
Protection class	II
Colour housing	White
Type of control gear	Electronic transformer
Material housing	Plastic
Material cover	Plastic, opal
Degree of protection (IP)	IP20
Control gear included	Yes
Max. system power	12 W
Rated ambient temperature according to IEC62722-2-1	-20 - 45 °C



10.12.2019

Subject to changes and printing errors

No dim function	Yes
Power factor	0.9
Dimming method	On/Off
Input	
Nominal voltage	200 - 240 V
Voltage type	AC
Installation	
Height/depth	65 mm
Width	240 mm
Outer diameter	240 mm
Conductor cross section	2.5 mm ²
Connection type	Plug clamp
Number of poles	4
Suitable for wall mounting	Yes
Suitable for surface mounting	Yes
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Brand	Quick Install
Imported by	The Light Group
General data	
Type of grid	Matt