



SLC MOON Ø300 WH 1650TED 830 IP40 110°

«Dark Light» Anti-glare dimmable LED ceiling lamp reduces glare index due to how the LED is placed. Quick connection, slim and nice design enables wide use.



Light technic	
Product ID	3300007
Beam angle	100 °, Extreme wide beam >80° °
Colour temperature	3000 K, 3000 - 3000 K
Efficacy	110 lm/W
Luminous flux (lm)	1650
MacAdam (SDCM)	3
Glare (UGR)	UGR<23
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Light sharing	Symmetric
With light source	Yes
Rated luminous flux according to IEC 62722-2-1	1650 lm
Colour of light	White
Rated life time L70/B50 at 25 °C	110000 Hours
Rated life time L80/B10 at 25 °C	50000 Hours
Light distributor	Focal lens
Luminaire efficacy	110 lm/W
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
CE	Yes
Dimmable	Yes
RoHs	Yes
Protection class	II
Colour housing	White
Type of control gear	LED operating device current-controlled
Material housing	Plastic
Material cover	Plastic, transparent
Impact strength	IK08
Degree of protection (IP)	IP20
Control gear included	Yes

14.06.2021

Subject to changes and printing errors

Max. system power	15 W
Rated ambient temperature according to IEC62722-2-1	-10 - 40 °C
Filament test according to IEC 60695-2-11	650 °C - 30 s
Dimming phase cut-off	Yes
Dimming depending on control gear	No
Power factor	0.9
Dimming method	Trailing edge
Input	
Voltage type	AC/DC
Nominal voltage	200 - 240 V
Installation	
Height/depth	32 mm
Type of installation	Surface
Outer diameter	300 mm
Conductor cross section	2.5 mm ²
Connection type	Plug clamp
Suitable for suspended mounting	No
Suitable for built-in mounting	No
Suitable for surface mounting	Yes
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC
General data	
GTIN	7070938054591
Type of grid	Matt
M-pack length	330 mm
F-pack length	330 mm