

SLC MOON Ø300 WH 1650TED 3000K CRI80 IP40 110°



Dimmable (TED) ceiling light in fresh and modern design. Recommended dimmer: SLC SmartOne (S24019). For mounting directly on the ceiling. Slim design with only 32 mm height. The recessed LED diodes ensure low glare. Quick connection for easy installation. Multifunctional application.

Light technic	
Product ID	3300007
Beam angle	Extreme wide beam >80° °
Expected lifetime	50 000
Light reduction	L80B10
Glare (UGR)	UGR<23
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Light sharing	Symmetric
With light source	Yes
Colour temperature	3000.0 - 3000.0 K
Rated luminous flux according to IEC 62722-2-1	1650 lm
Colour of light	White
Rated life time L70/B50 at 25 °C	110000 Hours
Light distributor	Focal lens
Luminaire efficacy	110 lm/W
Technical data	
CE	Yes
Protection class	II
Colour housing	White
Type of control gear	LED operating device current-controlled
Material housing	Plastic
Material cover	Plastic, transparent
Impact strength	IK08
Degree of protection (IP)	IP20
Control gear included	Yes
Max. system power	15 W
Rated ambient temperature according to IEC62722-2-1	-10.0 - 40.0 °C
Filament test according to IEC 60695-2-11	650 °C - 30 s
Dimming phase cut-off	Yes



26.04.2024

Subject to changes and printing errors

Power factor	0.9
Dimming interface	Trailing edge
Input	
Voltage type	AC
Nominal voltage	200.0 - 240.0 V
Installation	
Height/depth	32 mm
Outer diameter	300 mm
Conductor cross section	2.5 mm ²
Connection type	Push-in clamp
Suitable for suspended mounting	No
Suitable for built-in mounting	No
Suitable for surface mounting	Yes
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC
F-Pak	
F-pack width	40 mm
F-pack height	330 mm
F-pack weight	800 g
F-pack length	330 mm
General data	
Type of grid	Matt
Rated power	15 W
M-Pak	
M-pack weight	9700 g
M-pack height	330 mm
M-pack width	440 mm
M-pack length	330 mm
Number	10