



# GF DESIGN TUBO DOWNLIGHT R62 TED

Unique Scandinavian design. Deep recessed COB. Quick connection.

Light technic	
Product ID	B_3234512
Beam angle	Medium beam 21-40°
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour of light	White
Rated life time L70/B50 at 25 °C	50000 Hours
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Protection class	II
Surface protection	Powder coating
Suitable for lamp power	9 - 9
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP54
Control gear included	Yes
Max. system power	10 W
Adjustability	Not adjustable
Rated ambient temperature according to IEC62722-2-1	-10 - 45 °C
Dimming phase cut-off	Yes
Input	
Voltage type	AC/DC
Nominal voltage	230 - 230 V
Output	
LED nominal current at constant current	230 - 230 mA



Installation	
Built-in width	62 mm
Built-in height/depth	43 mm
Length	70 mm
Built-in length	62 mm
Outer diameter	70 mm
Conductor cross section	0.35 mm <sup>2</sup>
Connection type	Plug clamp
Built-in diameter	62 mm
Number of poles	3
Suitable for built-in mounting	Yes
Connectable conductor cross section	0.75 - 2.5 mm <sup>2</sup>
Type of wiring	Suitable for through wiring
logistics data	
Imported by	The Light Group
Brand	SLC
General data	
Pallet length	1200 mm
M-pack length	585 mm
F-pack length	115 mm