

# SLC LED STRIP RED CC 60 5M 8MM

## 4,3W 130LM IP20



Low wattage single colour strip with Constant Current technology that protects each LED diode against voltage drop and gives more uniform light on long distances

Light technic	
Product ID	S10103
Beam angle	120
Lamp type	LED not exchangeable
Lamp power per meter	4.3 W/m
Number of nodes per meter	60 LED`s
Colour of light	Red
Luminous flux per meter	130 lm/m
Rated life time L70/B10 at 25 °C	100000 Hours
Rated life time L70/B50 at 25 °C	120000 Hours
Rated life time L80/B10 at 25 °C	60000 Hours
Rated life time L80/B50 at 25 °C	75000 Hours
Rated life time L90/B10 at 25 °C	30000 Hours
Rated life time L90/B50 at 25 °C	35000 Hours
Lamp power per foot	1.3 W
Number of nodes per foot	18
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Cutting point, every	100 mm
IP class	IP20
LED-Strip length	5 m
Max length per connection:	20 meter m
Protection class	II
Type of control gear	LED operating device voltage-controlled
Degree of protection (IP)	IP20
Lamp voltage	24 - 24 V
Max. system power	21.5 W
Input	
Voltage type	DC
Installation	
Length of particular segments	100 mm
Height/depth	2 mm



06.05.2021

Subject to changes and printing errors

<b>Length</b>	5000 mm
<b>Width</b>	8 mm
<b>Mounting method</b>	Surface mounting/recessed mounting
<b>Model</b>	Strip
<b>Conductor cross section</b>	0.35 mm <sup>2</sup>
<b>Connection type</b>	Solder
<b>Self-adhesive</b>	Yes
<b>Number of poles</b>	2
<b>With protective cover</b>	No
<b>With connection set</b>	No
<b>With end piece</b>	No
<b>Type of wiring</b>	Ending
<b>logistics data</b>	
<b>Brand</b>	SLC
<b>Imported by</b>	The Light Group
<b>General data</b>	
<b>GTIN</b>	7070938055956