

# SLC LED-STRIPS STANDARD CV 9,6 W CRI90



SLC LED-Strip Standard is a bestseller with high colour rendering, CRI 90. Excellent light output and low power. Suitable for most installations as direct, indirect, decorative, and background lighting.

Light technic	
Product ID	B_S11010
Beam angle	120 °, 120
Colour rendering index (CRI /Ra)	90
Expected lifetime	60 000
Number of LED`s per meter	120
Light reduction	L80B10
MacAdam (SDCM)	3
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Lamp power per meter	9.6 W/m
Number of nodes per meter	120 LED`s
Colour of light	White
Rated life time L70/B50 at 25 ° C	120000 Hours
Lamp power per foot	2.88 W
Number of nodes per foot	36
Technical data	
Exterior color	White
Cutting point, every	50 mm
Dimmable	Yes
Max length per connection:	5 meter m
Operating temperature	-10°C ~ +45°C °C
Rated power per meter	9.6 W/m
Protection class	II
Type of control gear	LED operating device voltage-controlled
Suitable for dimmer	Yes
Lamp voltage	24.0 - 24.0 V
Technology	Constant voltage (CV)
Input	
Electrical connection (Input)	2 meter wire in each end
Voltage type	DC



Installation	
Length of particular segments	50 mm
Mounting method	Surface mounting/recessed mounting
Model	Strip
Conductor cross section	0.35 mm <sup>2</sup>
Connection type	Solder
Self-adhesive	Yes
Number of poles	2
With protective cover	No
With connection set	No
With end piece	No
Type of wiring	Ending
logistics data	
Imported by	The Light Group
Brand	SLC