

SLC LED STRIP GREEN CV 120 5M

10MM 9,6W 680LM IP67



Single colour LED- strip, 9,6W/m. Suitable for visual decorative and accentual effects.

| Light technic | |
|----------------------------------|---|
| Product ID | S11106 |
| Beam angle | 120 |
| Lamp type | LED not exchangeable |
| Lamp power per meter | 9.6 W/m |
| Number of nodes per meter | 120 LED's |
| Colour of light | Green |
| Luminous flux per meter | 680 lm/m |
| Rated life time L70/B50 at 25 °C | 120000 Hours |
| Lamp power per foot | 2.88 W |
| Luminaire efficacy | 70.8 lm/W |
| Number of nodes per foot | 36 |
| Technical data | |
| Cutting point, every | 50 mm |
| IP class | IP67 |
| LED-Strip length | 5 m |
| Max length per connection: | 5 meter m |
| Protection class | II |
| Type of control gear | LED operating device voltage-controlled |
| Suitable for dimmer | Yes |
| Degree of protection (IP) | IP67 |
| Lamp voltage | 24.0 - 24.0 V |
| Max. system power | 48 W |
| Input | |
| Voltage type | DC |
| Installation | |
| Length of particular segments | 50 mm |
| Height/depth | 4 mm |
| Length | 5000 mm |
| Width | 12 mm |
| Mounting method | Surface mounting/recessed mounting |
| Model | Strip |



| | |
|-------------------------|-----------------|
| Conductor cross section | 0.35 mm2 |
| Connection type | Solder |
| Self-adhesive | Yes |
| Number of poles | 2 |
| With protective cover | Yes |
| With connection set | No |
| With end piece | No |
| Type of wiring | Ending |
| logistics data | |
| Imported by | The Light Group |
| Brand | SLC |
| D-Pak | |
| D-pack length | 360 mm |
| D-pack weight | 13200 g |
| D-pack height/diameter | 380 mm |
| D-pack quantity | 20 pcs |
| D-pack width | 320 mm |
| F-Pak | |
| F-pack width | 300 mm |
| F-pack height | 18 mm |
| F-pack weight | 650 g |
| F-pack length | 310 mm |