

# SLC LED STRIP RED CV 120 5M 10MM

## 9,6W 260LM IP20



Low wattage single colour LED- strip, 9,6W/m. Suitable for visual decorative and accentual effects.

| Light technic                                |   |
|--|---|
| Product ID                                   | S11103                                  |
| Beam angle                                   | 120                                     |
| Lamp type                                    | LED not exchangeable                    |
| Lamp power per meter                         | 9.6 W/m                                 |
| Number of nodes per meter                    | 120 LED`s                               |
| Colour of light                              | Red                                     |
| Luminous flux per meter                      | 260 lm/m                                |
| Rated life time L70/B10 at 25 °C             | 100000 Hours                            |
| Rated life time L70/B50 at 25 °C             | 120000 Hours                            |
| Rated life time L80/B10 at 25 °C             | 60000 Hours                             |
| Rated life time L80/B50 at 25 °C             | 75000 Hours                             |
| Rated life time L90/B10 at 25 °C             | 30000 Hours                             |
| Rated life time L90/B50 at 25 °C             | 35000 Hours                             |
| Lamp power per foot                          | 2.88 W                                  |
| Number of nodes per foot                     | 36                                      |
| Energy efficiency class of the built-in lamp | A++, A+, A (LED)                        |
| Technical data                               |   |
| Cutting point, every                         | 50 mm                                   |
| IP class                                     | IP20                                    |
| LED-Strip length                             | 5 m                                     |
| Max length per connection:                   | 5 meter m                               |
| Protection class                             | II                                      |
| Type of control gear                         | LED operating device voltage-controlled |
| Degree of protection (IP)                    | IP20                                    |
| Lamp voltage                                 | 24 - 24 V                               |
| Max. system power                            | 48 W                                    |
| Input  |   |
| Voltage type                                 | DC                                      |
| Installation                                 |   |
| Length of particular segments                | 50 mm                                   |
| Height/depth                                 | 2 mm                                    |



06.05.2021

Subject to changes and printing errors

|                                |                                    |
|--------------------------------|------------------------------------|
| <b>Length</b>                  | 5000 mm                            |
| <b>Width</b>                   | 10 mm                              |
| <b>Mounting method</b>         | Surface mounting/recessed mounting |
| <b>Model</b>                   | Strip                              |
| <b>Conductor cross section</b> | 0.35 mm <sup>2</sup>               |
| <b>Connection type</b>         | Solder                             |
| <b>Self-adhesive</b>           | Yes                                |
| <b>Number of poles</b>         | 2                                  |
| <b>With protective cover</b>   | No                                 |
| <b>With connection set</b>     | No                                 |
| <b>With end piece</b>          | No                                 |
| <b>Type of wiring</b>          | Ending                             |
| logistics data                 |                                    |
| <b>Brand</b>                   | SLC                                |
| <b>Imported by</b>             | The Light Group                    |
| General data                   |                                    |
| <b>GTIN</b>                    | 7070938056212                      |