SLC LED STRIP RED CV 120 5M 10MM 9,6W 228LM IP67

C€

Single colour LED- strip, 9,6W/m. Suitable for visual decorative and accentual effects.

| Light technic | |
|--|---|
| Product ID | S11104 |
| Beam angle | 120 |
| Lamp type | LED not exchangeable |
| Lamp power per meter | 9.6 W/m |
| Number of nodes per meter | 120 LED`s |
| Colour of light | Red |
| Luminous flux per meter | 228 lm/m |
| Rated life time L70/B50 at 25 $^{\circ}$ C | 120000 Hours |
| Lamp power per foot | 2.88 W |
| Luminaire efficacy | 23.8 lm/W |
| Number of nodes per foot | 36 |
| Technical data | |
| Cutting point, every | 50 mm |
| IP class | IP67 |
| LED-Strip length | 5 m |
| Max length per connection: | 5 meter m |
| Protection class | II |
| Type of control gear | LED operating device voltage- controlled |
| Suitable for dimmer | Yes |
| Degree of protection (IP) | IP67 |
| Lamp voltage | 24.0 - 24.0 V |
| Max. system power | 48 W |
| | Input |
| Voltage type | DC |
| Installation | |
| Length of particular segments | 50 mm |
| Height/depth | 4 mm |
| Length | 5000 mm |
| Width | 12 mm |
| Mounting method | Surface mounting/recessed mounting |
| Model | Strip |
| | |



| Conductor cross section | 0.35 mm2 |
|--|--|
| Connection type | Solder |
| Self-adhesive | Yes |
| Number of poles | 2 |
| With protective cover | Yes |
| With connection set | No |
| With end piece | No |
| Type of wiring | Ending |
| logistics data | |
| Imported by | The Light Group |
| Brand | SLC |
| | |
| | D-Pak |
| D-pack length | D-Pak 360 mm |
| D-pack length D-pack weight | |
| | 360 mm |
| D-pack weight | 360 mm 13200 g |
| D-pack weight D-pack height/diameter | 360 mm 13200 g 380 mm |
| D-pack weight D-pack height/diameter D-pack quantity | 360 mm 13200 g 380 mm 20 pcs |
| D-pack weight D-pack height/diameter D-pack quantity | 360 mm 13200 g 380 mm 20 pcs 320 mm |
| D-pack weight D-pack height/diameter D-pack quantity D-pack width | 360 mm 13200 g 380 mm 20 pcs 320 mm |
| D-pack weight D-pack height/diameter D-pack quantity D-pack width F-pack width | 360 mm 13200 g 380 mm 20 pcs 320 mm F-Pak 300 mm |