



# SLC LED STRIP RED CV 120 5M 10MM

## 9,6W 234LM IP67

Low wattage single colour LED- strip, 9,6W/m. Suitable for visual decorative and accentual effects.

Light technic	
Product ID	S11104
Beam angle	120
Lamp type	LED not exchangeable
Lamp power per meter	9.6 W/m
Number of nodes per meter	120 LED`s
Colour of light	Red
Luminous flux per meter	234 lm/m
Rated life time L70/B10 at 25 °C	100000 Hours
Rated life time L70/B50 at 25 °C	120000 Hours
Rated life time L80/B10 at 25 °C	60000 Hours
Rated life time L80/B50 at 25 °C	75000 Hours
Rated life time L90/B10 at 25 °C	30000 Hours
Rated life time L90/B50 at 25 °C	35000 Hours
Lamp power per foot	2.88 W
Number of nodes per foot	36
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Cutting point, every	50 mm
IP class	IP67
LED-Strip length	5 m
Max length per connection:	5 meter m
Protection class	II
Type of control gear	LED operating device voltage-controlled
Degree of protection (IP)	IP67
Lamp voltage	24 - 24 V
Max. system power	48 W
Input	
Voltage type	DC
Installation	
Length of particular segments	50 mm
Height/depth	4 mm



06.05.2021

Subject to changes and printing errors

<b>Length</b>	5000 mm
<b>Width</b>	12 mm
<b>Mounting method</b>	Surface mounting/recessed mounting
<b>Model</b>	Strip
<b>Conductor cross section</b>	0.35 mm <sup>2</sup>
<b>Connection type</b>	Solder
<b>Self-adhesive</b>	Yes
<b>Number of poles</b>	2
<b>With protective cover</b>	Yes
<b>With connection set</b>	No
<b>With end piece</b>	No
<b>Type of wiring</b>	Ending
<b>logistics data</b>	
<b>Brand</b>	SLC
<b>Imported by</b>	The Light Group
<b>General data</b>	
<b>GTIN</b>	7070938056229