

SLC LED STRIP MONO CC 126 5M

12MM 10W 900LM 827 IP67

Professional LED-strip with high efficiency. Perfect for more significant projects, where light output is essential. Constant Current technology protects each LED against voltage drop.



Light technic	
Product ID	S13041
Beam angle	120 °, 120
Colour rendering index (CRI /Ra)	80
Expected lifetime	60 000
Number of LED`s per meter	126
Light reduction	L80B10
Efficacy	90 lm/W
Lumens pr. meter	900 lm
MacAdam (SDCM)	3
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	10 W/m
Number of nodes per meter	126 LED`s
Colour temperature	2700.0 - 2700.0 K
Colour of light	White
Luminous flux per meter	900 lm/m
Rated life time L70/B50 at 25 ° C	120000 Hours
Lamp power per foot	3 W
Number of nodes per foot	37.8
Technical data	
Exterior color	White
Cutting point, every	56 mm
Dimmable	Yes
IP class	IP67
LED-Strip length	5 m
Max length per connection:	12 meter m
Operating temperature	-10°C ~ +45°C °C
Rated power per meter	10 W/m
Protection class	II
Type of control gear	LED operating device voltage-controlled



Degree of protection (IP)	IP67
Lamp voltage	24.0 - 24.0 V
Max. system power	50 W
Technology	Constant voltage (CV)
Input	
Electrical connection (Input)	2 meter wire in each end
Voltage type	DC
Installation	
Length of particular segments	56 mm
Height/depth	4 mm
Height	4 mm
Length	5000 mm
Width	12 mm, 12 mm
Mounting method	Surface mounting/recessed mounting
Model	Strip
Conductor cross section	0.35 mm ²
Connection type	Solder
Self-adhesive	Yes
Number of poles	2
With protective cover	Yes
With connection set	No
With end piece	No
Type of wiring	Ending
logistics data	
Imported by	The Light Group
Brand	SLC