CE

SLC LED STRIP MONO CC 126 5M 10MM 15W 1540LM 830 IP54

Professional LED strip with high-efficiency, high-lumen output. Constant Current technology protects each LED against voltage drop, giving more uniform light at long distances.

Light technic	
Product ID	S13048
Beam angle	120
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	15 W/m
Number of nodes per meter	126 LED`s
Colour temperature	3000.0 - 3000.0 K
Colour of light	White
Luminous flux per meter	1540 lm/m
Rated life time L70/B50 at 25 $^\circ$ C	110000 Hours
Lamp power per foot	4.5 W
Number of nodes per foot	37.8
Technical data	
Cutting point, every	56 mm
IP class	IP54
LED-Strip length	5 m
Max length per connection:	10 meter m
Protection class	ll
Type of control gear	LED operating device voltage- controlled
Degree of protection (IP)	IP54
Lamp voltage	24.0 - 24.0 V
Max. system power	75 W
	Input
Voltage type	DC
Installation	
Length of particular segments	56 mm
Height/depth	2.5 mm
Length	5000 mm
Width	10 mm
Mounting method	Surface mounting/recessed mounting
Model	Strip



26.04.2024 Subject to changes and printing errors

Conductor cross section	0.35 mm2
Connection type	Solder
Self-adhesive	Yes
Number of poles	2
With protective cover	Yes
With connection set	No
With end piece	No
Type of wiring	Ending
logistics data	
Imported by	The Light Group
Brand	SLC

26.04.2024 Subject to changes and printing errors