



LED STRIP RGBW CV 60 5M 14MM

14,4W 490LM RGB/830 IP67

RGBW is a multicolour LED-strip, which also includes white light (3000K). Suitable for colourful, creative installations, which also give possibility to use white light.

| Light technic | |
|--|---|
| Product ID | S14006 |
| Beam angle | 120 |
| Colour rendering index CRI | 80-89 |
| Lamp type | LED not exchangeable |
| Lamp power per meter | 14.4 W/m |
| Number of nodes per meter | 60 LED`s |
| Colour of light | RGBW |
| Luminous flux per meter | 490 lm/m |
| Rated life time L70/B50 at 25 °C | 50000 Hours |
| Lamp power per foot | 4.32 W |
| Number of nodes per foot | 18 |
| Energy efficiency class of the built-in lamp | A++, A+, A (LED) |
| Technical data | |
| Cutting point, every | 100 mm |
| Protection class | II |
| Type of control gear | LED operating device voltage-controlled |
| Degree of protection (IP) | IP67 |
| Max. system power | 72 W |
| Power factor | 0.95 |
| Input | |
| Voltage type | DC |
| Installation | |
| Length of particular segments | 100 mm |
| Height/depth | 4 mm |
| Length | 5000 mm |
| Width | 14 mm |
| Mounting method | Surface mounting/recessed mounting |
| Model | Strip |
| Conductor cross section | 0.35 mm ² |
| Connection type | Solder |



10.12.2019

Subject to changes and printing errors

| | |
|------------------------------|-----------------|
| Self-adhesive | Yes |
| Number of poles | 5 |
| With protective cover | No |
| Lowest bending radius | 25 mm |
| With connection set | No |
| With end piece | No |
| Type of wiring | Ending |
| logistics data | |
| Imported by | The Light Group |
| Brand | SLC |
| General data | |
| GTIN | 7070938056649 |
| Pallet length | 1200 mm |
| M-pack length | 360 mm |
| F-pack length | 383 mm |