

SLC LED STRIP TW CV 120 5M 10MM

14,4W 1120LM 2400-6500K CRI80 IP20



Tuneable White (TW): LED light with dynamic white color; adjustable color temperature between 2400K and 6500K.

Light technic	
Product ID	S14007
Beam angle	120
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	14.4 W/m
Number of nodes per meter	120 LED`s
Colour temperature	2400.0 - 6500.0 K
Colour of light	White
Luminous flux per meter	1120 lm/m
Rated life time L70/B50 at 25 °C	120000 Hours
Lamp power per foot	4.32 W
Luminaire efficacy	77.8 lm/W
Number of nodes per foot	36
Technical data	
Cutting point, every	100 mm
IP class	IP20
LED-Strip length	5 m
Max length per connection:	5 meter m
Protection class	II
Type of control gear	LED operating device voltage-controlled
Suitable for dimmer	Yes
Degree of protection (IP)	IP20
Lamp voltage	24.0 - 24.0 V
Max. system power	72 W
Power factor	0.95
Input	
Voltage type	DC
Installation	
Length of particular segments	100 mm
Height/depth	2 mm
Length	5000 mm



Width	10 mm
Mounting method	Surface mounting/recessed mounting
Model	Strip
Conductor cross section	0.35 mm ²
Connection type	Solder
Self-adhesive	Yes
Number of poles	3
With protective cover	No
Lowest bending radius	25 mm
With connection set	No
With end piece	No
Type of wiring	Ending
logistics data	
Imported by	The Light Group
Brand	SLC
D-Pak	
D-pack length	550 mm
D-pack weight	17340 g
D-pack volume	71.775 dm ³
D-pack height/diameter	290 mm
D-pack quantity	80 pcs
D-pack width	450 mm
F-Pak	
F-pack width	190 mm
F-pack height	12 mm
F-pack weight	210 g
F-pack length	205 mm
M-Pak	
M-pack weight	4210 g
M-pack height	250 mm
M-pack width	220 mm
M-pack length	360 mm
Number	20
General data	
Pallet length	1200 mm