



# SLC LED STRIP FLEX MONO CV 60

## 5M 6MM 4,8W 410LM 830 IP20

Flex is our most flexible low wattage LED-strip designed for indirect lighting. Suitable for visual decorative effects where construction is bent.

Light technic	
Product ID	S14011
Beam angle	120
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	4.8 W/m
Number of nodes per meter	60 LED's
Colour temperature	3000.0 - 3000.0 K
Colour of light	White
Luminous flux per meter	410 lm/m
Rated life time L70/B10 at 25 ° C	90000 Hours
Rated life time L70/B50 at 25 ° C	110000 Hours
Rated life time L80/B10 at 25 ° C	60000 Hours
Rated life time L80/B50 at 25 ° C	70000 Hours
Rated life time L90/B10 at 25 ° C	29000 Hours
Rated life time L90/B50 at 25 ° C	35000 Hours
Lamp power per foot	1.44 W
Number of nodes per foot	18
Technical data	
Cutting point, every	100 mm
IP class	IP20
LED-Strip length	5 m
Max length per connection:	5 meter m
Protection class	II
Type of control gear	LED operating device voltage-controlled
Degree of protection (IP)	IP20
Lamp voltage	24.0 - 24.0 V
Max. system power	24 W
Power factor	0.95
Input	



19.09.2021

Subject to changes and printing errors

<b>Voltage type</b>	DC
<b>Installation</b>	
<b>Length of particular segments</b>	100 mm
<b>Height/depth</b>	2 mm
<b>Length</b>	5000 mm
<b>Width</b>	6 mm
<b>Mounting method</b>	Surface mounting/recessed mounting
<b>Model</b>	Strip
<b>Conductor cross section</b>	0.35 mm <sup>2</sup>
<b>Connection type</b>	Solder
<b>Self-adhesive</b>	Yes
<b>Number of poles</b>	2
<b>With protective cover</b>	No
<b>Lowest bending radius</b>	20 mm
<b>With connection set</b>	No
<b>With end piece</b>	No
<b>Type of wiring</b>	Ending
<b>logistics data</b>	
<b>Imported by</b>	The Light Group
<b>Brand</b>	SLC
<b>General data</b>	
<b>D-pack length</b>	550 mm
<b>GTIN</b>	7070938056694
<b>Pallet length</b>	1200 mm
<b>M-pack length</b>	260 mm
<b>F-pack length</b>	205 mm