

SLC LED STRIP FLEX MONO CV 60

5M 6MM 4,8W 410LM 3000K CRI80

IP20



Flex is our most flexible low-power LED strip designed for indirect lighting. Suitable for visual deco effects and for highlighting details in cases where bends and curves are a fact.

| Light technic | |
|-----------------------------------|---|
| Product ID | S14011 |
| Beam angle | 120 |
| Colour rendering index CRI | 80-89 |
| Lamp type | LED not exchangeable |
| Lamp power per meter | 4.8 W/m |
| Number of nodes per meter | 60 LED's |
| Colour temperature | 3000.0 - 3000.0 K |
| Colour of light | White |
| Luminous flux per meter | 410 lm/m |
| Rated life time L70/B50 at 25 ° C | 110000 Hours |
| Lamp power per foot | 1.44 W |
| Luminaire efficacy | 85.4 lm/W |
| Number of nodes per foot | 18 |
| Technical data | |
| Cutting point, every | 100 mm |
| IP class | IP20 |
| LED-Strip length | 5 m |
| Max length per connection: | 5 meter m |
| Protection class | II |
| Type of control gear | LED operating device voltage-controlled |
| Suitable for dimmer | Yes |
| Degree of protection (IP) | IP20 |
| Lamp voltage | 24.0 - 24.0 V |
| Max. system power | 24 W |
| Power factor | 0.95 |
| Input | |
| Voltage type | DC |
| Installation | |
| Length of particular segments | 100 mm |



| | |
|-------------------------|------------------------------------|
| Height/depth | 2 mm |
| Length | 5000 mm |
| Width | 6 mm |
| Mounting method | Surface mounting/recessed mounting |
| Model | Strip |
| Conductor cross section | 0.35 mm ² |
| Connection type | Solder |
| Self-adhesive | Yes |
| Number of poles | 2 |
| With protective cover | No |
| Lowest bending radius | 20 mm |
| With connection set | No |
| With end piece | No |
| Type of wiring | Ending |
| logistics data | |
| Imported by | The Light Group |
| Brand | SLC |
| D-Pak | |
| D-pack length | 550 mm |
| D-pack weight | 17600 g |
| D-pack volume | 71.775 dm ³ |
| D-pack height/diameter | 450 mm |
| D-pack quantity | 100 pcs |
| D-pack width | 290 mm |
| F-Pak | |
| F-pack width | 190 mm |
| F-pack height | 12 mm |
| F-pack weight | 170 g |
| F-pack length | 205 mm |
| M-Pak | |
| M-pack weight | 4400 g |
| M-pack height | 250 mm |
| M-pack width | 220 mm |
| M-pack length | 260 mm |
| Number | 25 |
| EPREL Data | |
| EPREL Energy Class | F |
| General data | |
| Pallet length | 1200 mm |

26.04.2024
Subject to changes and printing errors