



# SLC LED STRIP DOUBLE SIDE MONO CV 120 5M 5MM 9,6W 640LM 827 IP20

This LED-strip sends light beam sidewise in both directions. Good colour rendering, light output and low wattage.

Light technic	
Product ID	S14016
Beam angle	120
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	9.6 W/m
Number of nodes per meter	120 LED's
Colour temperature	2700.0 - 2700.0 K
Colour of light	White
Luminous flux per meter	640 lm/m
Rated life time L80/B10 at 25 ° C	50000 Hours
Lamp power per foot	2.88 W
Number of nodes per foot	36
Technical data	
Cutting point, every	50 mm
IP class	IP20
LED-Strip length	5 m
Max length per connection:	5 meter m
Protection class	II
Type of control gear	LED operating device voltage-controlled
Degree of protection (IP)	IP20
Lamp voltage	24.0 - 24.0 V
Max. system power	48 W
Power factor	0.95
Input	
Voltage type	DC
Installation	
Length of particular segments	50 mm
Height/depth	2 mm
Length	5000 mm
Width	5 mm
Mounting method	Surface mounting/recessed mounting



19.09.2021

Subject to changes and printing errors

<b>Model</b>	Strip
<b>Conductor cross section</b>	0.35 mm <sup>2</sup>
<b>Connection type</b>	Solder
<b>Self-adhesive</b>	Yes
<b>Number of poles</b>	2
<b>With protective cover</b>	No
<b>Lowest bending radius</b>	20 mm
<b>With connection set</b>	No
<b>With end piece</b>	No
<b>Type of wiring</b>	Ending
<b>logistics data</b>	
<b>Imported by</b>	The Light Group
<b>Brand</b>	SLC
<b>General data</b>	
<b>D-pack length</b>	550 mm
<b>GTIN</b>	7070938056748
<b>Pallet length</b>	1200 mm
<b>M-pack length</b>	260 mm
<b>F-pack length</b>	205 mm