

SLC LED STRIP DOUBLE SIDE MONO

CV 120 5M 5MM 9,6W 650LM 3000K

CRI80 IP20



Double Side is an LED strip with lateral light distribution in both directions. For use in installations where side light is required instead of traditional uplighting.

Light technic	
Product ID	S14017
Beam angle	120
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	9.6 W/m
Number of nodes per meter	120 LED`s
Colour temperature	3000.0 - 3000.0 K
Colour of light	White
Luminous flux per meter	650 lm/m
Lamp power per foot	2.88 W
Luminaire efficacy	67.7 lm/W
Number of nodes per foot	36
Technical data	
Cutting point, every	50 mm
IP class	IP20
LED-Strip length	5 m
Max length per connection:	5 meter m
Protection class	II
Type of control gear	LED operating device voltage-controlled
Suitable for dimmer	Yes
Degree of protection (IP)	IP20
Lamp voltage	24.0 - 24.0 V
Max. system power	48 W
Power factor	0.95
Input	
Voltage type	DC
Installation	
Length of particular segments	50 mm
Height/depth	2 mm



Length	5000 mm
Width	5 mm
Mounting method	Surface mounting/recessed mounting
Model	Strip
Conductor cross section	0.35 mm ²
Connection type	Solder
Self-adhesive	Yes
Number of poles	2
With protective cover	No
Lowest bending radius	20 mm
With connection set	No
With end piece	No
Type of wiring	Ending
logistics data	
Imported by	The Light Group
Brand	SLC
D-Pak	
D-pack length	550 mm
D-pack weight	17600 g
D-pack volume	71.775 dm ³
D-pack height/diameter	450 mm
D-pack quantity	100 pcs
D-pack width	290 mm
F-Pak	
F-pack width	190 mm
F-pack height	12 mm
F-pack weight	170 g
F-pack length	205 mm
M-Pak	
M-pack weight	4400 g
M-pack height	250 mm
M-pack width	220 mm
M-pack length	260 mm
Number	25
EPREL Data	
EPREL Energy Class	F
General data	
Pallet length	1200 mm