

SLC LED STRIP 90° MONO CV 120 5M

10MM 9,6W 1100LM 4000K CRI80 IP20



LED strip with adjustable LEDs; each individual LED can be adjusted which way it should light up.

Light technic	
Product ID	S14021
Beam angle	120
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	9.6 W/m
Number of nodes per meter	120 LED`s
Colour temperature	4000.0 - 4000.0 K
Colour of light	White
Luminous flux per meter	1100 lm/m
Rated life time L70/B50 at 25 ° C	110000 Hours
Lamp power per foot	4.2 W
Luminaire efficacy	114.6 lm/W
Number of nodes per foot	36
Technical data	
Cutting point, every	50 mm
IP class	IP20
LED-Strip length	5 m
Max length per connection:	5 meter m
Protection class	II
Type of control gear	LED operating device voltage-controlled
Suitable for dimmer	Yes
Degree of protection (IP)	IP20
Lamp voltage	24.0 - 24.0 V
Max. system power	70 W
Power factor	0.95
Input	
Voltage type	DC
Installation	
Length of particular segments	50 mm
Height/depth	2 mm
Length	5000 mm



Width	10 mm
Mounting method	Surface mounting/recessed mounting
Model	Strip
Conductor cross section	0.35 mm ²
Connection type	Solder
Self-adhesive	Yes
Number of poles	2
With protective cover	No
Lowest bending radius	20 mm
With connection set	No
With end piece	No
Type of wiring	Ending
logistics data	
Imported by	The Light Group
Brand	SLC
D-Pak	
D-pack length	550 mm
D-pack weight	17600 g
D-pack volume	71.775 dm ³
D-pack height/diameter	450 mm
D-pack quantity	100 pcs
D-pack width	290 mm
F-Pak	
F-pack width	190 mm
F-pack height	12 mm
F-pack weight	170 g
F-pack length	205 mm
M-Pak	
M-pack weight	4400 g
M-pack height	250 mm
M-pack width	220 mm
M-pack length	260 mm
Number	25
EPREL Data	
EPREL Energy Class	F
General data	
Pallet length	1200 mm