

SLC LED STRIP 3D MONO CV 3X60

5M 10MM 14,4W 1150LM 827 IP20



This LED-strip sends light beam sidewise in both directions and upwards.
Good colour rendering, light output and low wattage.

Light technic	
Product ID	S14031
Beam angle	180
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	14.4 W/m
Number of nodes per meter	180 LED` s
Colour temperature	2700.0 - 2700.0 K
Colour of light	White
Luminous flux per meter	1150 lm/m
Rated life time L80/B10 at 25 ° C	50000 Hours
Lamp power per foot	4.32 W
Number of nodes per foot	54
Technical data	
Cutting point, every	100 mm
IP class	IP20
LED-Strip length	5 m
Max length per connection:	5 meter m
Protection class	II
Type of control gear	LED operating device voltage-controlled
Degree of protection (IP)	IP20
Lamp voltage	24.0 - 24.0 V
Max. system power	72 W
Power factor	0.95
Input	
Voltage type	DC
Installation	
Length of particular segments	100 mm
Height/depth	2 mm
Length	5000 mm
Width	10 mm
Mounting method	Surface mounting/recessed mounting



Model	Strip
Conductor cross section	0.35 mm ²
Connection type	Solder
Self-adhesive	Yes
Number of poles	2
With protective cover	No
Lowest bending radius	20 mm
With connection set	No
With end piece	No
Type of wiring	Ending
logistics data	
Imported by	The Light Group
Brand	SLC
General data	
D-pack length	550 mm
GTIN	7070938056892
Pallet length	1200 mm
M-pack length	260 mm
F-pack length	205 mm