SLC SMARTONE Z-WAVE CONTROLLER CV 4X5A 12-36V

Z-Wave constant voltage controller 12-36V with 4 channels. Compatible with all universal z-wave master controllers.



Technical data	
Product ID	B_S25001
Exterior color	White
Dimming curve (LED)	Logarithmic
Dimming range	0-100% %
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 45°C)	50000 Hours
Tc	75 °C
Protection class	II
Housing	Plastic housing
Programmable	No
Degree of protection (IP)	IP20
Operating method	Other
Dimming method	Pulse Width Modulation (PWM)
Dimming interface	Z-wave
Input	
Electrical connection (Input)	L`N quick connection
Max input current	20.5 A
Input voltage	12.0 - 36.0 V
Output	
RGBW	No
Max total output power at 24VDC	480 W
RGB	No
Output power per channel at 24VDC	120 W
Mono	No
Output power per channel	[60.0, 180.0] W
Max. output current	5 A
Max total output power	720 W
Tunable White	No
Output voltage	12.0 - 36.0 V
Max output current	20 A
Installation	
Length	170 mm

The Light Group AS, Sagmyra 2A, 4624 Kristiansand S, Norway
Tel.: +47 38 00 21 01 | E-Mail : post@tlg.no **www.tlg.no**

Height	28 mm
Width	54 mm
Model	Static
Built-in	Yes
Surface-mounted	No
Suitable for outdoor use	No
DIN rail mounting	No
logistics data	
Brand	SLC
Imported by	The Light Group

The Light Group AS, Sagmyra 2A, 4624 Kristiansand S, Norway
Tel.: +47 38 00 21 01 | E-Mail : post@tlg.no **www.tlg.no**