

SLC DL03 SQUARE DOWNLIGHT



Stylish downlight with smooth square design. Tilttable (45°) in all directions. Very high CRI>95 enhances vivid colors in any environment.

Light technic	
Product ID	B_SL-1036
Beam angle	Wide beam 41-80° °
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour of light	White
Rated life time L70/B50 at 25 °C	50000 Hours
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Surface protection	Powder coating
Suitable for lamp power	9 - 9
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Control gear included	Yes
Max. system power	9 W
Adjustability	Swivelling
Rated ambient temperature according to IEC62722-2-1	-10 - 40 °C
Dimming phase cut-off	Yes
Dimming method	Trailing edge
Input	
Nominal voltage	220 - 240 V
Voltage type	AC/DC
Output	
LED nominal current at constant current	350 - 350 mA
Installation	



14.06.2021

Subject to changes and printing errors

Height/depth	40 mm
Built-in height/depth	40 mm
Length	95 mm
Width	95 mm
Conductor cross section	0.35 mm ²
Connection type	Pinching contact
Built-in diameter	83 mm
Suitable for suspended mounting	No
Number of poles	3
Suitable for wall mounting	No
Suitable for built-in mounting	Yes
Connectable conductor cross section	0.75 - 1.5 mm ²
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Brand	SLC