



# SLC DL03 SQUARE DOUBLE DOWNLIGHT

Stylish downlight with smooth square design. Tilttable (45°) in all directions.  
Very high CRI>95 enhances vivid colors in any environment.



Light technic	
Product ID	B_SL-1042
Beam angle	Medium beam 21-40°
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour of light	White
Rated life time L70/B50 at 25 °C	50000 Hours
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Protection class	II
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Control gear included	Yes
Surface brushed	Yes
Max. system power	18 W
Adjustability	Swivelling
Rated ambient temperature according to IEC62722-2-1	-20 - 50 °C
Dimming depending on control gear	Yes
Dimming method	Trailing edge
Input	
Nominal voltage	220 - 240 V
Voltage type	AC/DC
Installation	
Height/depth	40 mm

14.06.2021

Subject to changes and printing errors

<b>Built-in width</b>	85 mm
<b>Built-in height/depth</b>	38 mm
<b>Length</b>	180 mm
<b>Built-in length</b>	170 mm
<b>Width</b>	95 mm
<b>Conductor cross section</b>	0.35 mm <sup>2</sup>
<b>Connection type</b>	Plug clamp
<b>Suitable for suspended mounting</b>	No
<b>Number of poles</b>	3
<b>Suitable for wall mounting</b>	No
<b>Suitable for built-in mounting</b>	Yes
<b>Connectable conductor cross section</b>	0.5 - 2.5 mm <sup>2</sup>
<b>Type of wiring</b>	Suitable for through wiring
<b>Suitable for ceiling mounting</b>	Yes
logistics data	
<b>Brand</b>	SLC