

SLC DL03 RECT R BL 2X695TED 927

IP44 45°

Stylish downlight with smooth square design. Tilttable (45°) in all directions.
Very high CRI>95 enhances vivid colors in any environment.



Light technic	
Product ID	SL-1044
Beam angle	Wide beam 41-80° °
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	2700.0 - 2700.0 K
Rated luminous flux according to IEC 62722-2-1	1390 lm
Colour of light	White
Luminous flux	1390.0 - 1390.0 lm
Rated life time L70/B50 at 25 °C	50000 Hours
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Technical data	
Protection class	II
Colour housing	Black
Surface protection	Powder coating
Suitable for lamp power	18.0 - 18.0
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Control gear included	Yes
Surface brushed	Yes
Max. system power	18 W
Adjustability	Swivelling
Rated ambient temperature according to IEC62722-2-1	-20.0 - 50.0 °C
Dimming phase cut-off	Yes
Input	
Voltage type	AC

20.04.2024
Subject to changes and printing errors

Nominal voltage	220.0 - 240.0 V
Installation	
Height/depth	40 mm
Built-in width	85 mm
Built-in height/depth	38 mm
Length	180 mm
Built-in length	170 mm
Width	95 mm
Conductor cross section	0.35 mm ²
Connection type	Push-in clamp
Suitable for suspended mounting	No
Number of poles	3
Suitable for built-in mounting	Yes
Connectable conductor cross section	0.5 - 2.5 mm ²
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Brand	SLC