

SLC DL03 SURFACE SINGLE



Stylish surface-mounted downlight box. Tilttable (45°) in all directions. Very high CRI>95 enhances vivid colors in any environment.

Light technic	
Product ID	B_SL-1045
Beam angle	Wide beam 41-80° °
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	2700.0 - 2700.0 K
Colour of light	White
Luminous flux	650.0 - 650.0 lm
Rated life time L70/B50 at 25 °C	50000 Hours
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Luminaire efficacy	72 lm/W
Technical data	
Protection class	I
Colour housing	White
Surface protection	Powder coating
Suitable for lamp power	9.0 - 9.0
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Glass transparent
Degree of protection (IP)	IP40
Control gear included	Yes
Max. system power	9 W
Adjustability	Swivelling
Rated ambient temperature according to IEC62722-2-1	-20.0 - 50.0 °C
Dimming phase cut-off	Yes
Power factor	0.95
Input	
Voltage type	AC



Nominal voltage	220.0 - 240.0 V
Installation	
Height/depth	82 mm
Length	126 mm
Width	126 mm
Conductor cross section	0.35 mm ²
Connection type	Push-in clamp
Suitable for suspended mounting	No
Number of poles	3
Suitable for built-in mounting	No
Connectable conductor cross section	0.75 - 1.5 mm ²
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Brand	SLC