



DL03 SURFACE DOBULE

Stylish surface-mounted downlight box. Tilttable (45°) in all directions. Very high CRI>95 enhances vivid colors in any environment.

Light technic	
Product ID	B_SL-1046
Beam angle	Wide beam 41-80°
Lamp efficacy	72 lm/W
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	2700 - 2700 K
Colour of light	White
Luminous flux	1300 - 1300 lm
Rated life time L70/B50 at 25 °C	50000 Hours
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Luminaire efficacy	72 lm/W
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Protection class	I
Colour housing	White
Surface protection	Powder coating
Suitable for lamp power	18 - 18
Type of control gear	LED operating device voltage-controlled
Material housing	Aluminium
Material cover	Glass transparent
Degree of protection (IP)	IP40
Control gear included	Yes
Adjustability	Rotating and swivelling
Rated ambient temperature according to IEC62722-2-1	-20 - 50 °C
Dimming DALI	Yes
Dimming phase cut-off	Yes
Power factor	0.9



07.12.2019

Subject to changes and printing errors

Input	
Nominal voltage	220 - 240 V
Voltage type	AC/DC
Output	
LED nominal current at constant current	380 - 380 mA
Installation	
Height/depth	82 mm
Length	230 mm
Width	126 mm
Conductor cross section	0.35 mm ²
Connection type	Plug clamp
Number of poles	3
Suitable for surface mounting	Yes
Connectable conductor cross section	0.75 - 1.5 mm ²
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Brand	SLC