

# SLC DL03 SURFACE DOUBLE



Stylish surface-mounted downlight box. Tilttable (45°) in all directions. Very high CRI>95 enhances vivid colors in any environment.

Light technic	
Product ID	B_SL-1046
Beam angle	Wide beam 41-80° °
Lamp efficacy	72 lm/W
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	2700 - 2700 K
Colour of light	White
Luminous flux	1300 - 1300 lm
Rated life time L70/B50 at 25 °C	50000 Hours
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Luminaire efficacy	72 lm/W
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Protection class	I
Colour housing	White
Surface protection	Powder coating
Suitable for lamp power	18 - 18
Type of control gear	LED operating device voltage-controlled
Material housing	Aluminium
Material cover	Glass transparent
Degree of protection (IP)	IP40
Control gear included	Yes
Max. system power	18 W
Adjustability	Swivelling
Rated ambient temperature according to IEC62722-2-1	-20 - 50 °C
Dimming DALI	Yes
Dimming phase cut-off	Yes



14.06.2021

Subject to changes and printing errors

<b>Power factor</b>	0.9
<b>Dimming method</b>	Trailing edge
Input	
<b>Nominal voltage</b>	220 - 240 V
<b>Voltage type</b>	AC/DC
Output	
<b>LED nominal current at constant current</b>	380 - 380 mA
Installation	
<b>Height/depth</b>	82 mm
<b>Length</b>	230 mm
<b>Width</b>	126 mm
<b>Conductor cross section</b>	0.35 mm <sup>2</sup>
<b>Connection type</b>	Plug clamp
<b>Suitable for suspended mounting</b>	No
<b>Number of poles</b>	3
<b>Suitable for wall mounting</b>	No
<b>Suitable for built-in mounting</b>	No
<b>Connectable conductor cross section</b>	0.75 - 1.5 mm <sup>2</sup>
<b>Type of wiring</b>	Suitable for through wiring
<b>Suitable for ceiling mounting</b>	Yes
logistics data	
<b>Brand</b>	SLC