

# SLC PRO LOW DOWNLIGHT



The downlight is available in two sizes and the LED can have four different lumen outputs, depending on the driver. (Driver is not included)

Light technic	
Product ID	B_SLC1001
Beam angle	Wide beam 41-80° °
Reflector	High-gloss
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Technical data	
Protection class	II
Colour housing	Aluminium
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Impact strength	IK08
Degree of protection (IP)	IP20
Surface brushed	Yes
Adjustability	Not adjustable
Rated ambient temperature according to IEC62722-2-1	-20.0 - 45.0 °C
Power factor	0.9
Input	
Voltage type	AC
Nominal voltage	220.0 - 240.0 V
Installation	
Conductor cross section	0.35 mm <sup>2</sup>
Connection type	Push-in clamp
Suitable for suspended mounting	No
Number of poles	2



18.04.2024

Subject to changes and printing errors

Suitable for built-in mounting	Yes
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC