

SLC PRO HIGH DOWNLIGHT TED



Light technic	
Product ID	B_SLC1010
Beam angle	Medium beam 21-40° °
Reflector	High-gloss
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	3000.0 - 4000.0 K
Colour of light	White
Luminous flux	3000.0 - 4000.0 lm
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Technical data	
Protection class	II
Colour housing	Aluminium
Surface protection	Powder coating
Suitable for lamp power	15.0 - 30.0
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP20
Max. system power	30 W
Adjustability	Not adjustable
Rated ambient temperature according to IEC62722-2-1	-20.0 - 45.0 °C
Power factor	0.9
Input	
Voltage type	DC
Nominal voltage	220.0 - 240.0 V
Installation	
Suitable for suspended mounting	No
Number of poles	2
Suitable for built-in mounting	Yes



Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC