

LED CEILING S250 1100TED 840 IP54 OP



Dimmable with TED (Trailing edge) dimmers. Recommended dimmer: SLC SmartOne (S24019). With opal shield for a comfortable lighting experience. Wall or ceiling mounting. Perfect for hallways, stairs, bathrooms, and wardrobes. Push connector with strain relief. Quick installation.



Light technic	
Product ID	SLC1062
Beam angle	120 °, Open beam /diffuse °
Expected lifetime	50 000
Light reduction	L80B10
MacAdam (SDCM)	3
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Light sharing	Symmetric
With light source	Yes
Colour temperature	4000.0 - 4000.0 K
Rated luminous flux according to IEC 62722-2-1	1100 lm
Colour of light	White
Light distributor	Diffuser lens/optic/panel
Luminaire efficacy	92 lm/W
Technical data	
CE	Yes
Exterior color	White
IP class	IP54
Operating temperature	-10°C ~ +45°C °C
Protection class	II
Colour housing	White
With movement sensor	No
Suitable for lamp power	12.0 - 12.0
Type of control gear	LED operating device current-controlled
With light sensor	No
Material housing	Plastic
Material cover	Plastic, opal
Impact strength	IK08
Degree of protection (IP)	IP54
Luminaire with limited surface	No

23.04.2024
Subject to changes and printing errors

temperature, sign "D"	
Covering of the luminaire with thermally insulating material possible	No
Control gear included	Yes
Fit for workplace according to EN 12464-1	No
Max. system power	12 W
Rated ambient temperature according to IEC62722-2-1	-20.0 - 50.0 °C
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	Yes
Dimming phase cut-on	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dim function	No
Dimming DSI	No
Power factor	0.9
Dimming interface	Trailing edge
Input	
Power factor	0.9
Voltage type	AC
Nominal voltage	220.0 - 240.0 V
Installation	
Height/depth	53 mm
Length	250 mm
Width	250 mm
Type of installation	Surface
Outer diameter	250 mm
Connection type	Push-in clamp
Suitable for suspended mounting	No

23.04.2024
Subject to changes and printing errors

Number of poles	3
Suitable for built-in mounting	No
Suitable for surface mounting	Yes
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC
General data	
Type of grid	Matt
With air slots	No
Suitable for emergency lighting	No
Suitable for light line configuration	No
M-Pak	
M-pack weight	15200 g
M-pack height	540 mm
M-pack width	280 mm
M-pack length	660 mm
Number	10