



SLC LED CEILING S300 1550TED 827 IP54 OP

Dimmable LED ceiling lamp

Light technic	
Product ID	SLC1063
Beam angle	Open beam/diffuse °
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	2700 - 2700 K
Rated luminous flux according to IEC 62722-2-1	1550 lm
Colour of light	White
Rated life time L80/B10 at 25 °C	50000 Hours
Light distributor	Diffuser lens/optic/panel
Luminaire efficacy	86 lm/W
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Protection class	II
Colour housing	White
With movement sensor	No
Suitable for lamp power	18 - 18
Type of control gear	LED operating device current-controlled
With light sensor	No
Material housing	Plastic
Material cover	Plastic, opal
Impact strength	IK08
Degree of protection (IP)	IP54
Luminaire with limited surface temperature, sign "D"	No
Covering of the luminaire with thermally insulating material possible	No
Control gear included	Yes
Fit for workplace according to EN 12464-1	No
Max. system power	18 W
Rated ambient temperature according to	-20 - 50 °C



27.01.2020

Subject to changes and printing errors

IEC62722-2-1

Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming potentiometer (integrated)	No
Dimming GPRS	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	Yes
Dimming phase cut-on	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dim function	No
Dimming depending on control gear	No
Dimming DSI	No
Power factor	0.9
Input	
Voltage type	AC/DC
Nominal voltage	220 - 240 V
Output	
LED nominal current at constant current	225 - 225 mA
Installation	
Height/depth	58 mm
Length	300 mm
Width	300 mm
Outer diameter	300 mm
Connection type	Plug clamp
Suitable for suspended mounting	No
Number of poles	3
Suitable for wall mounting	Yes
Suitable for built-in mounting	No
Suitable for surface mounting	Yes
Type of wiring	Suitable for through wiring

27.01.2020
Subject to changes and printing errors

Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC
General data	
GTIN	7070938055079
With air slots	No
Suitable for emergency lighting	No
Suitable for light line configuration	No