



## SLC DL04 DOWNLIGHT R83 TED

Retracted LED for creating comfortable ambient. Tilt-able (25°) round downlight with smooth design. Suitable for outside use (IP54). Available in black or white.



Light technic	
Product ID	B_SLC1101
Beam angle	36 °, Medium beam 21-40° °
Colour rendering index (CRI/Ra)	90
Type of light source	LED
MacAdam (SDCM)	3
Tilt-able	25 °
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour of light	White
Rated life time L80/B10 at 25 °C	50000 Hours
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Type of control signal	Trailing Edge
Dimmable	Yes
Dimming range	1-100% %
Driver output current	230 mA
IP class	IP54
Operating temperature	-10°C ~ +45°C °C
System consumption	10 W
Protection class	II
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP54
Control gear included	Yes

06.05.2021

Subject to changes and printing errors

Max. system power	10 W
Adjustability	Swivelling
Rated ambient temperature according to IEC62722-2-1	-10 - 40 °C
Dimming phase cut-off	Yes
Power factor	0.9
Dimming method	Trailing edge
Input	
Electrical connection (Input)	L`L`N`N quick connection
Voltage type	AC/DC
Strain relief	Yes
Nominal voltage	220 - 240 V
Installation	
Cut-out hole (Ø)	83 mm
Height/depth	55 mm
Built-in width	83 mm
Height	55 mm
Built-in height/depth	55 mm
Length	95 mm
Width	95 mm, 95 mm
Installation depth	55 mm
Type of installation	Recessed
Outer diameter	95 mm
Conductor cross section	0.35 mm <sup>2</sup>
Connection type	Plug clamp
Built-in diameter	83 mm
Suitable for suspended mounting	No
Number of poles	3
Suitable for wall mounting	No
Suitable for built-in mounting	Yes
Connectable conductor cross section	0.75 - 2.5 mm <sup>2</sup>
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Pcs carton	48
Imported by	The Light Group
Brand	SLC
General data	
Pallet length	1200 mm
M-pack length	460 mm

06.05.2021  
Subject to changes and printing errors

Rated power	10 W
F-pack length	111 mm