

# SLC DL04 ROUND X1 R83 TED



The SLC DL04 Round X1 is a tiltable recessed luminaire, providing an excellent lighting experience and a discrete look. A modern, deeply recessed LED chip provides a pleasant light with low glare and good colour rendering.

Light technic	
Product ID	B_SLC1101
Beam angle	36 °, Medium beam 21-40° °
Expected lifetime	50 000
Light reduction	L80B10
MacAdam (SDCM)	3
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Technical data	
CE	Yes
IP class	IP54
Operating temperature	-10°C ~ +45°C °C
Protection class	II
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP54
Control gear included	Yes
Max. system power	10 W
Adjustability	Swivelling
Rated ambient temperature according to IEC62722-2-1	-10.0 - 40.0 °C
Dimming phase cut-off	Yes
Power factor	0.9
Dimming interface	Trailing edge



25.04.2024

Subject to changes and printing errors

Input	
Electrical connection (Input)	L`L`N`N quick connection
Power factor	0.9
Voltage type	AC
Nominal voltage	220.0 - 240.0 V
Installation	
Height/depth	55 mm
Built-in width	83 mm
Height	55 mm
Built-in height/depth	55 mm
Length	95 mm
Width	95 mm, 95 mm
Outer diameter	95 mm
Conductor cross section	0.35 mm <sup>2</sup>
Connection type	Push-in clamp
Suitable for suspended mounting	No
Number of poles	3
Suitable for built-in mounting	Yes
Connectable conductor cross section	0.75 - 2.5 mm <sup>2</sup>
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC
F-Pak	
F-pack width	110 mm
F-pack height	90 mm
F-pack weight	376 g
F-pack length	111 mm
M-Pak	
M-pack weight	18300 g
M-pack height	295 mm
M-pack width	460 mm
M-pack length	460 mm
Number	48
General data	
Pallet length	1200 mm
Rated power	10 W