

SLC DL04 R83 BL 650TED 2700K

CRI90 IP54 36°



The SLC DL04 Round X1 is a tiltable recessed luminaire, providing an excellent lighting experience and a discrete look. A modern, deeply recessed LED chip provides a pleasant light with low glare and good colour rendering.

Light technic	
Product ID	SLC1103
Beam angle	36 °, Medium beam 21-40° °
Expected lifetime	50 000
Light reduction	L80B10
Efficacy	65 lm/W
Luminous flux (lm)	650
MacAdam (SDCM)	3
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	2700.0 - 2700.0 K
Rated luminous flux according to IEC 62722-2-1	650 lm
Colour of light	White
Luminous flux	650.0 - 650.0 lm
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Technical data	
CE	Yes
Exterior color	Black
IP class	IP54
Operating temperature	-10°C ~ +45°C °C
Protection class	II
Colour housing	Black
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent



26.04.2024

Subject to changes and printing errors

Degree of protection (IP)	IP54
Control gear included	Yes
Max. system power	10 W
Adjustability	Swivelling
Rated ambient temperature according to IEC62722-2-1	-10.0 - 40.0 °C
Dimming phase cut-off	Yes
Power factor	0.9
Dimming interface	Trailing edge
Input	
Electrical connection (Input)	L`L`N`N quick connection
Voltage type	AC
Nominal voltage	220.0 - 240.0 V
Power factor	0.9
Installation	
Height/depth	55 mm
Built-in width	83 mm
Height	55 mm
Built-in height/depth	55 mm
Length	95 mm
Width	95 mm, 95 mm
Outer diameter	95 mm
Conductor cross section	0.35 mm ²
Connection type	Push-in clamp
Suitable for suspended mounting	No
Number of poles	3
Suitable for built-in mounting	Yes
Connectable conductor cross section	0.75 - 2.5 mm ²
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC
F-Pak	
F-pack width	110 mm
F-pack height	90 mm
F-pack weight	376 g
F-pack length	111 mm
EPREL Data	
EPREL Energy Class	F

26.04.2024
Subject to changes and printing errors

General data	
Pallet length	1200 mm
Rated power	10 W
M-Pak	
M-pack length	460 mm
Number	48
M-pack weight	18300 g
M-pack height	295 mm
M-pack width	460 mm