



SLC DL04 DOWNLIGHT (WITHOUT DRIVER)

Retracted LED for creating comfortable ambient. CRI>90 enhances vivid colors in any environment.

Light technic	
Product ID	B_SLC1105
Beam angle	Medium beam 21-40°
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour of light	White
Rated life time L80/B10 at 25 °C	50000 Hours
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
CE	Yes
RoHS	Yes
SELV	Yes
Protection class	III
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP54
Max. system power	10 W
Adjustability	Swivelling
Rated ambient temperature according to IEC62722-2-1	-20 - 45 °C
Dimming depending on control gear	Yes
Input	
Nominal voltage	18 - 36 V
Voltage type	DC
Output	



LED nominal current at constant current	230 - 230 mA
Installation	
Cut-out hole (Ø)	83 mm
Height/depth	55 mm
Built-in width	83 mm
Built-in height/depth	55 mm
Width	95 mm
Outer diameter	95 mm
Conductor cross section	0.35 mm ²
Connection type	Plug clamp
Built-in diameter	83 mm
Suitable for suspended mounting	No
Suitable for wall mounting	No
Suitable for built-in mounting	Yes
Type of wiring	Ending
Suitable for ceiling mounting	Yes
logistics data	
Brand	SLC
Imported by	The Light Group