



SLC DL04 DOWNLIGHT (WITHOUT DRIVER)

Retracted LED for creating comfortable ambient. CRI>90 enhances vivid colors in any environment.

Light technic	
Product ID	B_SLC1105
Beam angle	Medium beam 21-40° °
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Technical data	
CE	Yes
Protection class	III
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP54
Max. system power	10 W
Adjustability	Swivelling
Rated ambient temperature according to IEC62722-2-1	-20.0 - 45.0 °C
Input	
Nominal voltage	18.0 - 36.0 V
Voltage type	DC
Installation	
Height/depth	55 mm
Built-in width	83 mm
Built-in height/depth	55 mm
Width	95 mm
Outer diameter	95 mm



24.04.2024

Subject to changes and printing errors

Conductor cross section	0.35 mm2
Connection type	Push-in clamp
Suitable for suspended mounting	No
Suitable for built-in mounting	Yes
Type of wiring	Ending
Suitable for ceiling mounting	Yes
logistics data	
Brand	SLC
Imported by	The Light Group