

# SLC DL04 NO DRIVER R83 BL 927

## IP54 36°



Retracted LED for creating comfortable ambient. CRI>90 enhances vivid colors in any environment.

Light technic	
Product ID	SLC1107
Beam angle	Medium beam 21-40° °
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	2700.0 - 2700.0 K
Rated luminous flux according to IEC 62722-2-1	700 lm
Colour of light	White
Luminous flux	650.0 - 650.0 lm
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Luminaire efficacy	65 lm/W
Technical data	
CE	Yes
RoHS	Yes
SELV	Yes
Protection class	III
Colour housing	Black
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP54
Max. system power	10 W
Adjustability	Swivelling
Rated ambient temperature according to IEC62722-2-1	-10.0 - 40.0 °C
Input	
Voltage type	DC



29.03.2024

Subject to changes and printing errors

Nominal voltage	18.0 - 36.0 V
Installation	
Height/depth	55 mm
Built-in width	83 mm
Built-in height/depth	55 mm
Width	95 mm
Outer diameter	95 mm
Conductor cross section	0.35 mm <sup>2</sup>
Connection type	Push-in clamp
Suitable for suspended mounting	No
Suitable for built-in mounting	Yes
Type of wiring	Ending
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC