

SLC ONE360 DOWNLIGHT R68-83 (WITHOUT DRIVER)



One360° Downlight Base without a driver. Please also choose your preferred driver. Tilts 30° in all directions (360°). Can be mounted into insulation, up to the moisture barrier

Light technic	
Product ID	B_SLC1132
Beam angle	36 °, Medium beam 21-40° °
MacAdam (SDCM)	3
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour of light	White
Colour consistency (MacAdam ellipse)	SDCM3
Light distributor	Reflector
Technical data	
CE	Yes
IP class	IP44
Operating temperature	-10°C ~ +45°C °C
Protection class	II
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP44
Control gear included	No
Max. system power	8 W
Adjustability	Rotating and swivelling
Rated ambient temperature according to IEC62722-2-1	-10.0 - 40.0 °C
Dimming phase cut-off	Yes
Power factor	0.9
Input	
Electrical connection (Input)	L`N quick connection
Voltage type	DC



16.04.2024

Subject to changes and printing errors

Nominal voltage	18.0 - 38.0 V
Installation	
Height/depth	46 mm
Built-in width	68 mm
Height	46 mm
Built-in height/depth	46 mm
Length	90 mm
Width	90 mm, 90 mm
Can be installed directly into the insulation	Yes
Type of installation	Recessed
Outer diameter	90 mm
Conductor cross section	0.35 mm ²
Connection type	Push-in clamp
Suitable for suspended mounting	No
Number of poles	3
Suitable for built-in mounting	Yes
Connectable conductor cross section	0.75 - 2.5 mm ²
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC
F-Pak	
F-pack weight	106 g