

SLC ONE360 R68-83 BL 550-1030LM

927 IP44 36°



One360° Downlight Base without a driver. Please also choose your preferred driver. Tilts 30° in all directions (360°). Can be mounted into insulation, up to the moisture barrier

Light technic	
Product ID	SLC1134
Beam angle	36 °, Medium beam 21-40° °
MacAdam (SDCM)	3
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	2700.0 - 2700.0 K
Rated luminous flux according to IEC 62722-2-1	1030 lm
Colour of light	White
Luminous flux	550.0 - 1030.0 lm
Colour consistency (MacAdam ellipse)	SDCM3
Light distributor	Reflector
Technical data	
CE	Yes
Exterior color	Black
IP class	IP44
Operating temperature	-10°C ~ +45°C °C
Protection class	II
Colour housing	Black
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP44
Control gear included	No
Max. system power	8 W
Adjustability	Rotating and swivelling
Rated ambient temperature according	-10.0 - 40.0 °C



26.04.2024

Subject to changes and printing errors

to IEC62722-2-1	
Dimming phase cut-off	Yes
Power factor	0.9
Input	
Electrical connection (Input)	L`N quick connection
Voltage type	DC
Nominal voltage	18.0 - 38.0 V
Installation	
Height/depth	46 mm
Built-in width	68 mm
Height	46 mm
Built-in height/depth	46 mm
Length	90 mm
Width	90 mm, 90 mm
Can be installed directly into the insulation	Yes
Outer diameter	90 mm
Conductor cross section	0.35 mm ²
Connection type	Push-in clamp
Suitable for suspended mounting	No
Number of poles	3
Suitable for built-in mounting	Yes
Connectable conductor cross section	0.75 - 2.5 mm ²
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC
F-Pak	
F-pack height	50 mm
F-pack weight	164 g
F-pack length	100 mm
D-Pak	
D-pack quantity	50 pcs
D-pack width	290 mm
D-pack length	590 mm
D-pack weight	12500 g
D-pack height/diameter	370 mm
M-Pak	
M-pack length	100 mm

26.04.2024
Subject to changes and printing errors

Number	1
M-pack weight	230 g
M-pack height	65 mm
M-pack width	100 mm