

# SLC ONE360 R68-83 BL 560-1020LM

## 930 IP44 36°



One360° Downlight Base without a driver. Please also choose your preferred driver. Tilts 30° in all directions (360°). Can be mounted into insulation, up to the moisture barrier



Light technic	
Product ID	SLC1135
Beam angle	36 °, Medium beam 21-40° °
Colour rendering index (CRI/Ra)	90
MacAdam (SDCM)	3
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	3000.0 - 3000.0 K
Rated luminous flux according to IEC 62722-2-1	1020 lm
Colour of light	White
Luminous flux	560.0 - 1020.0 lm
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Technical data	
CE	Yes
Exterior color	Black
Dimmable	Yes
IP class	IP44
Operating temperature	-10°C ~ +45°C °C
RoHs	Yes
Protection class	II
Colour housing	Black
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP44
Control gear included	No

29.03.2024  
Subject to changes and printing errors

Max. system power	8 W
Adjustability	Rotating and swivelling
Rated ambient temperature according to IEC62722-2-1	-10.0 - 40.0 °C
RAL Colour	RAL9005
Dimming phase cut-off	Yes
Power factor	0.9
Input	
Electrical connection (Input)	L`N quick connection
Voltage type	DC
Nominal voltage	18.0 - 38.0 V
Installation	
Height/depth	46 mm
Built-in width	68 mm
Height	46 mm
Built-in height/depth	46 mm
Length	90 mm
Width	90 mm, 90 mm
Can be installed directly into the insulation	Yes
Type of installation	Recessed
Outer diameter	90 mm
Conductor cross section	0.35 mm <sup>2</sup>
Connection type	Push-in clamp
Suitable for suspended mounting	No
Number of poles	3
Suitable for built-in mounting	Yes
Connectable conductor cross section	0.75 - 2.5 mm <sup>2</sup>
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC
F-Pak	
F-pack height	50 mm
F-pack weight	164 g
F-pack length	100 mm
D-Pak	
D-pack quantity	50 pcs
D-pack width	290 mm
D-pack length	590 mm

29.03.2024  
Subject to changes and printing errors

D-pack weight	12500 g
D-pack height/diameter	370 mm
M-Pak	
M-pack length	100 mm
Number	1
M-pack weight	230 g
M-pack height	65 mm
M-pack width	100 mm