



SLC ONESOFT DOWNLIGHT R68-83 (WITHOUT DRIVER)

OneSoft Downlight Base without a driver. Please choose your preferred driver. Can be mounted into insulation, up to the moisture barrier.

Light technic	
Product ID	B_SLC1137
Beam angle	Medium beam 21-40° °
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Rated life time L90/B10 at 25 °C	50000 Hours
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Protection class	III
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Max. system power	8 W
Adjustability	Not adjustable
Rated ambient temperature according to IEC62722-2-1	-10 - 40 °C
Dimming depending on control gear	Yes
Input	
Voltage type	DC
Installation	
Height/depth	46 mm
Built-in width	68 mm
Built-in height/depth	46 mm
Width	90 mm
Outer diameter	90 mm
Conductor cross section	0.35 mm ²



28.11.2020

Subject to changes and printing errors

Connection type	Plug clamp
Built-in diameter	68 mm
Suitable for suspended mounting	No
Suitable for wall mounting	No
Suitable for built-in mounting	Yes
Type of wiring	Ending
Suitable for ceiling mounting	Yes
logistics data	
Brand	SLC
Imported by	The Light Group