



# SLC ONESoft DOWNLIGHT R68-83 (WITHOUT DRIVER)

OneSoft Downlight Base without a driver. Please choose your preferred driver. Can be mounted into insulation, up to the moisture barrier.

Light technic	
Product ID	B_SLC1137
Beam angle	Medium beam 21-40° °
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Technical data	
Protection class	III
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Max. system power	8 W
Adjustability	Not adjustable
Rated ambient temperature according to IEC62722-2-1	-10.0 - 40.0 °C
Input	
Voltage type	DC
Installation	
Height/depth	46 mm
Built-in width	68 mm
Built-in height/depth	46 mm
Width	90 mm
Outer diameter	90 mm
Conductor cross section	0.35 mm <sup>2</sup>
Connection type	Push-in clamp
Suitable for suspended mounting	No
Suitable for built-in mounting	Yes



26.04.2024

Subject to changes and printing errors

Type of wiring	Ending
Suitable for ceiling mounting	Yes
logistics data	
Brand	SLC
Imported by	The Light Group