

# SLC ONESOFT R68-83 WH 570-950LM 927 IP44 36°



OneSoft Downlight Base without a driver. Please choose your preferred driver. Can be mounted into insulation, up to the moisture barrier.

Light technic	
Product ID	SLC1137
Beam angle	Medium beam 21-40° °
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	2700.0 - 2700.0 K
Rated luminous flux according to IEC 62722-2-1	950 lm
Colour of light	White
Luminous flux	570.0 - 950.0 lm
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Luminaire efficacy	75 lm/W
Technical data	
Protection class	III
Colour housing	White
Surface protection	Powder coating
Suitable for lamp power	8.0 - 8.0
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Max. system power	8 W
Adjustability	Not adjustable
Rated ambient temperature according to IEC62722-2-1	-10.0 - 40.0 °C
Input	
Voltage type	DC
Nominal voltage	220.0 - 240.0 V
Installation	
Height/depth	46 mm



20.04.2024

Subject to changes and printing errors

Built-in width	68 mm
Built-in height/depth	46 mm
Width	90 mm
Outer diameter	90 mm
Conductor cross section	0.35 mm <sup>2</sup>
Connection type	Push-in clamp
Suitable for suspended mounting	No
Suitable for built-in mounting	Yes
Connectable conductor cross section	0.35 - 0.35 mm <sup>2</sup>
Type of wiring	Ending
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC
D-Pak	
D-pack length	590 mm
D-pack weight	9200 g
D-pack height/diameter	370 mm
D-pack quantity	50 pcs
D-pack width	290 mm
M-Pak	
M-pack weight	165 g
M-pack height	65 mm
M-pack width	100 mm
M-pack length	100 mm
Number	1
F-Pak	
F-pack height	50 mm
F-pack weight	96 g
F-pack length	100 mm