



# SLC LED-PANEL TUNABLE WHITE R600

LED-panel with dimmable light - and adjustable CCT



Light technic	
Product ID	B_SLC8711
Beam angle	Extreme wide beam >80° °
Lamp holder	Other
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	3000 - 6500 K
Rated luminous flux according to IEC 62722-2-1	3200 lm
Colour of light	White
Rated life time L70/B50 at 25 °C	50000 Hours
Light distributor	Diffuser lens/optic/panel
Luminaire efficacy	89 lm/W
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Colour housing	White
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Degree of protection (IP)	IP20
Control gear included	No
Max. system power	36 W
Rated ambient temperature according to IEC62722-2-1	-10 - 40 °C
Dimming depending on control gear	Yes
Power factor	0.9
Input	
Nominal voltage	220 - 240 V
Voltage type	AC
Installation	
Height/depth	8 mm
Built-in width	600 mm

05.07.2020

Subject to changes and printing errors

<b>Built-in height/depth</b>	8 mm
<b>Length</b>	600 mm
<b>Built-in length</b>	600 mm
<b>Width</b>	600 mm
<b>Connection type</b>	Plug clamp
<b>Suitable for suspended mounting</b>	Yes
<b>Number of poles</b>	3
<b>Suitable for built-in mounting</b>	Yes
<b>Suitable for surface mounting</b>	Yes
<b>Type of wiring</b>	Suitable for through wiring
<b>Suitable for ceiling mounting</b>	Yes
logistics data	
<b>Brand</b>	SLC
<b>Imported by</b>	The Light Group