

SLC LED-PANEL R600 BASE 4400LM TUNEABLE WHITE 40W MP

LED-panel with dimmable light - and adjustable CCT



| Light technic | |
|---|--|
| Product ID | SLC8714 |
| Beam angle | Open beam/diffuse ° |
| Lamp holder | Other |
| Colour rendering index CRI | 80-89 |
| Lamp type | LED not exchangeable |
| Light outlet | Direct |
| Light sharing | Symmetric |
| With light source | Yes |
| Colour temperature | 2700.0 - 6000.0 K |
| Rated luminous flux according to IEC 62722-2-1 | 3200 lm |
| Colour of light | White |
| Rated life time L70/B50 at 25 °C | 50000 Hours |
| Light distributor | Diffuser lens/optic/panel |
| Luminaire efficacy | 110 lm/W |
| Technical data | |
| Exterior color | White |
| Protection class | III |
| Colour housing | White |
| Suitable for lamp power | 40.0 - 40.0 |
| Type of control gear | LED operating device current-controlled |
| Material housing | Aluminium |
| Material cover | Plastic, structured |
| Degree of protection (IP) | IP20 |
| Control gear included | No |
| Max. system power | 40 W |
| Rated ambient temperature according to IEC62722-2-1 | -10.0 - 40.0 °C |
| Power factor | 0.9 |
| Input | |
| Voltage type | DC |
| Nominal voltage | 8.0 - 48.0 V |
| Installation | |
| | |

28.03.2024
Subject to changes and printing errors

| | |
|---------------------------------|-----------------------------|
| Height/depth | 8 mm |
| Built-in width | 600 mm |
| Built-in height/depth | 8 mm |
| Length | 600 mm |
| Built-in length | 600 mm |
| Width | 600 mm |
| Connection type | Push-in clamp |
| Suitable for suspended mounting | Yes |
| Number of poles | 3 |
| Suitable for built-in mounting | Yes |
| Suitable for surface mounting | Yes |
| Type of wiring | Suitable for through wiring |
| Suitable for ceiling mounting | Yes |
| logistics data | |
| Imported by | The Light Group |
| Brand | SLC |
| General data | |
| Type of grid | Matt |