



## LED-PANEL ECO II

ECO II is one of our most sold luminaires! With a very attractive price /quality ratio. Stable high lumen output over time (L80B10). Long lifetime and 5 year warranty. Driver is sold separately.

Light technic	
Product ID	B_SLC8730
Beam angle	Extreme wide beam >80°
Lamp holder	Other
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour of light	White
Rated life time L70/B10 at 25 °C	70000 Hours
Rated life time L80/B10 at 25 °C	50000 Hours
Light distributor	Diffuser lens/optic/panel
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Protection class	III
Colour housing	White
Suitable for lamp power	36 - 36
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Degree of protection (IP)	IP20
Max. system power	36 W
Dimming depending on control gear	Yes
Power factor	0.95
Input	
Nominal voltage	220 - 240 V
Voltage type	AC
Output	
LED nominal current at constant current	900 - 900 mA
Installation	
Connection type	Plug clamp



<b>Suitable for suspended mounting</b>	Yes
<b>Number of poles</b>	3
<b>Suitable for built-in mounting</b>	Yes
<b>Type of wiring</b>	Suitable for through wiring
<b>Suitable for ceiling mounting</b>	Yes
<b>logistics data</b>	
<b>Brand</b>	SLC
<b>Imported by</b>	The Light Group
<b>General data</b>	
<b>Pallet length</b>	1200 mm
<b>M-pack length</b>	720 mm
<b>F-pack length</b>	700 mm